

SPECIFICATION

SHEET



PRODUCT: AVIUM

Overview

FLUX AVIUM FLUX AVIUM DIMMABLE LED strip light is an ideal replacement solution and fits neatly into existing fluorescent fittings. It offers a dimming capability integrated with a microwave sensor that offers instant light when activated and 10% output when not, offering 0 - 1000 lux. levels. This makes the dimmable option perfect for car parks where daily usage can vary without compromising security or safety. The FLUX AVIUM DIMMABLE LED strip light offers an instant beam of light to illuminate the desired area.

Additional Options – Inbuilt Emergency Pack

Built into casing of light fitting
3 hours lifespan in the case of power failure
Fits variation sizes of the Avium light fitting



Product Specification Table

Product Code	W	Lm	K	Ra		 L mm	 D mm	IP	PW /F		
AVI-650-10-2700-6000	10W	900	27-6000	>85	120°	650	130	IP65	0.9	-30~+40	>50,000
AVI-650-20-2700-6000	20W	1800	27-6000	>85	120°	650	130	IP65	0.9	-30~+40	>50,000
AVI-1270-16-2700-6000	16W	1440	27-6000	>85	120°	1270	130	IP65	0.9	-30~+40	>50,000
AVI-1270-20-2700-6000	20W	1800	27-6000	>85	120°	1270	130	IP65	0.9	-30~+40	>50,000
AVI-1270-40-2700-6000	40W	3600	27-6000	>85	120°	1270	130	IP65	0.9	-30~+40	>50,000
AVI-1570-25-2700-6000	25W	2250	27-6000	>85	120°	1570	130	IP65	0.9	-30~+40	>50,000



RoHS
Compliant

SPECIFICATION

SHEET



Product Code	W	Lm	K	Ra		 L mm	 D mm	IP	PW /F		
AVI-1570-50-2700-6000	50W	4500	27-6000	>85	120°	1570	130	IP65	0.9	-30~+40	>50,000
AVI-1570-60-2700-6000	60W	5400	27-6000	>85	120°	1570	130	IP65	0.9	-30~+40	>50,000
AVI-1860-30-2700-6000	30W	2700	27-6000	>85	120°	1860	165	IP65	0.9	-30~+40	>50,000
AVI-1860-60-2700-6000	60W	5400	27-6000	>85	120°	1860	165	IP65	0.9	-30~+40	>50,000